

DATA SHEET 20705.100.36100

Folajet QD-CL

A top coated transparent polyester film for high resolution photographic overlays and OHP's. This film is the ultimate in dimensional stability. It gives excellent flatness and colour contrast reproduction even when using high levels of ink, reducing the possibility of material distortion. The film is tear resistant and has excellent transparency properties for good see through clarity. Clear film offers excellent handling and dimensional stability properties. Images dry quickly. HP/RS is a removable paper stripe version for Hewlett Packard plotters that require sensors to detect clear film.

Printing Systems



Rolls

Art.Number	Nominal thickness (mm)	Width (mm)	Length (m)
20705.100.36100	0.100	610	30
20705.100.39200	0.100	914	30
20705.100.30700	0.100	1067	30
20705.100.32200	0.100	1270	30

Technical data

Characteristic

- Suitable for dye inks
- Suitable for piezo Ink Jet printer
- Suitable for thermal Ink Jet printer
- Good flatness
- Good stiffness
- High resolution
- No bleeding
- Tear resistant
- Fast dry

Finish

- Clear transparent

Specifications

Nominal thickness (mil)	4
Nominal thickness (mm)	0.100
Coating Printsides	Ink Jet
Width (inch)	24
Width (mm)	610
Printside	Matt Side
Length (ft)	98.43
Length (m)	30
Base Material	Polyester film
Packing quantity	1

Compatibility

- Suitable for most Ink Jet plotters using waterbased dye inks.
- Not compatible with oil and solvent based systems.

Handling

- Between 15-30°C and 30-70% r.h.
- Print side = matt white side
- A preconditioning period of 24 hours within the printing environment is recommended.
- Avoid fingerprints on printing side.

Storage

- Unopened in original packaging storage time is 1 year after shipment (under recommended storage conditions).
- Store in a cool and dry place at a room temperature of 15 - 25°C and at a humidity of 30 - 60%.

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. These shall be beyond our control, and be subject to your exclusive responsibility. The sale of our products shall be subject to our current General Terms and Conditions.

